

NASA TECH BRIEF



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Division, NASA, Code UT, Washington, D.C. 20546.

Interaction of Crippling and Torsional-Flexural Instabilities for Centrally Loaded Columns

An empirical technique is proposed for prediction of failure loads for centrally loaded columns, with thin-walled, open cross sections, which may fail by a combination of torsional-flexural buckling and crippling. Knowing the torsional-flexural buckling load and the crippling load for a column, their interaction can be predicted by a modification of the Johnson-Euler equation which is often used to relate crippling and Euler-type buckling:

$$P_c = P_{cs} - (P_{cs}^2 / 4P^*)$$

where P_c is the critical load (pounds) in combined crippling and torsional-flexural buckling, P_{cs} is the crippling load (pounds), and P^* is the critical load (pounds) in torsional-flexural buckling.

For such loaded columns that fail at stresses within the elastic range, the critical mode of failure is often torsional buckling or a combination of torsional and flexural buckling; it depends primarily on the geometry of the cross section and the length of the column.

There are methods for evaluation of this torsional or torsional-flexural buckling load for many variations in cross-sectional geometry and restraint conditions. All such methods, however, are based on the assumption that the cross-sectional shape does not change during buckling; that is, the theories consider primary failure of columns, rather than secondary failure, characterized by distortion of the cross section. Formulation of a theory incorporating coupling distortion and flexure with local buckling would be extremely complex.

For very short columns of thin-walled, open cross sections the failure stress is determined by the crippling-stress method, which does provide for local distortion of elements of the cross section.

Thus the coupling of these two failure modes by empirical means would provide a simple means for prediction of failure loads of columns that may fail by a combination of the torsional-flexural mode and the crippling mode. This approach has been followed already in the coupling of crippling and Euler buckling for closed sections (Johnson-Euler equation); the approach is the same in this coupling of crippling and torsional-flexural buckling. Although no attempt has been made to generate or correlate test data to confirm the accuracy of this technique, it is believed to be accurate.

Notes:

1. The following documentation may be obtained from:

Clearinghouse for Federal Scientific
and Technical Information
Springfield, Virginia 22151
Single document price \$3.00
(or microfiche \$0.65)

Reference:

NASA-CR-61287 (N69-32465), Interaction
of Crippling and Torsional-Flexural Instability
for Centrally Loaded Columns

2. Technical questions may be directed to:
Technology Utilization Officer
Code A&TS-TU
Marshall Space Flight Center
Huntsville, Alabama 35812
Reference: B70-10598

(continued overleaf)

Patent status:

No patent action is contemplated by NASA.

Source: J. C. Walls of
Brown Engineering Co., Inc.
under contract to
Marshall Space Flight Center
(MFS-20556)